

- **605.3 Breaker Box Clearance** - A working space of not less than 30 inches in width, 36 inches in depth and 78 inches in height shall be provided in front of electrical service equipment (panel). Where electrical service equipment is wider than 30 inches, the working space shall not be less than the width of the equipment.
- **605.5 Extension Cords** - Extension cords shall not be a substitute for permanent wiring.
- **605.6 Open Junction Boxes** - Open junction boxes and open wiring splices shall be prohibited. Approved covers shall be provided for all switch and outlet boxes. This included open breakers in breaker boxes, receptacles, light switches, etc.
- **901.6 Servicing Extinguishers** - Fire extinguishers shall be serviced annually and shall have a current service tag attached.
- **906.9 Extinguisher Placement** - Portable extinguishers having a gross weight not exceeding 40 pounds shall be installed so that its top is not more than 5 feet above the floor. Extinguishers having a gross weight exceeding 40 pounds shall be installed so that its top is not more than 3.5 feet above the floor and the bottom not less than 4 inches above floor.
- **1003.6 Obstructions to Exits** - Obstructions to exits shall not be placed in the required width and exits shall not be obstructed in any manner.
- **1006.1 Egress Illumination** - The means of egress, including the exit discharge, shall be illuminated at all times the building space served by the means of egress is occupied.
- **904.11.6.4 Hood Suppression Inspections** - Automatic fire extinguishing systems of commercial cooking equipment shall be serviced at least every 6 months and after activation of the system by a qualified individual.
- **Colleton County Ordinance 94-O-21**
  - D. Placement and Location of Address Numbers.
    - 1. When each house or building has been assigned its respective number or numbers, the owner, occupant or agent, shall place or cause to be placed upon each house or building controlled by him, the number or numbers assigned under the uniform addressing system as provided in this chapter.
    - 2. Such numbers shall be placed on existing buildings within thirty (30) days after owners receiving notification of the assigned proper number. The property owner shall pay for the cost of the assigned numbers. Residential numbers used shall not be less than four inches in height and **business numbers shall not be less than six inches in height**. These numbers shall be made of a durable and clearly visible material in a contrasting color for the building. A reflective material is preferred.
    - 3. Numbers shall be fixed in a conspicuous place immediately above, on or at the side of the proper door, so the number is clearly visible from the street or road. In the event the doorway does not face the street or road, the number shall be placed on the structure so it is visible from the direction of the road or driveway providing access to the structure. In cases where the home, building or structure is situated more than fifty (50) feet from the street or road, the number(s) shall also be placed near the walk, driveway, common entrance, fence, gatepost, or other appropriate place so as to be clearly visible from the street or road.